




Proposed North Elevation - 1:50



Proposed South Elevation - 1:50



Proposed East Elevation - 1:50



Proposed West Elevation - 1:50


- CONSTRUCTION / TYPES**
- 1) Wall Construction - Timber kit with Standing Seam Zinc cladding
 - 1mm Standing Seam Zinc cladding, RAL TBC.
 - 22mm OSB.
 - 50mm Cavity (50 x 50mm vertical timber battens)
 - 50mm Kingspan Thermawall Insulation.
 - Beadler Membrane.
 - 140mm Timber frame and Kingspan Thermawall Insulation.
 - 6mm ply sheath backing.
 - Vapour barrier with 38x50mm framing (service void).
 - 12.5mm plasterboard internal finish, (MR plasterboard to be installed in bathrooms, toilets, kitchen areas etc. where moisture build-up is more likely).
 - 2) Wall Construction - Timber kit with Rockpanel Cladding
 - 6mm Rockpanel cladding Panels
 - 50mm Cavity (50 x 50mm vertical timber battens)
 - 50mm Kingspan Thermawall Insulation.
 - 12mm Ply sheathing.
 - 140mm Timber frame and Kingspan Thermawall Insulation.
 - 6mm ply sheath backing.
 - Vapour barrier with 38x50mm framing (service void).
 - 12.5mm plasterboard internal finish, (MR plasterboard to be installed in bathrooms, toilets, kitchen areas etc. where moisture build-up is more likely).
 - 3) Wall Construction - Metal studs with Rockpanel cladding external finish.
 - Metal studs - Rockpanel cladding
 - 250mm Metal studs.
 - 50mm (repair rail system) (or equal and approved).
 - 6mm Rockpanel Aquamaine cladding panels.

- 4) Kalzip Roof Construction - Timber Deck.
 - Kalzip 65/400 (0.5mm) Top Sheet.
 - 15mm insulation (15 x 30mm compressed to 285mm).
 - E-90 Chip + S10 + S5.
 - 90mm deep top hat section.
 - Kalzip Clear VCL fixed to Timber Deck liner board (18mmarking board) on roof structure to structural engineer's specification and details.
- 5) Floor Construction
 - 75mm Sand/Cement Screenshot.
 - 150mm Concrete Floor Slab (to Structural Engineers details).
 - Kingspan Flostrate insulation.
 - DPM layer on behind hardcore.
 - Ground build up to Structural Engineers details
- 6) Foundations
 - Foundations blockwork outer leaf.
 - 50mm cavity - filled with concrete.
 - 62mm cavity - filled with insulation
 - 140mm blockwork inner leaf.

GENERAL NOTES

- Steelwork columns to structural engineer's specification.
- Roof structure to be in full accordance with structural engineer/timber kit supplier's design and specification.
- Foundations to structural engineer's specification.

12.10.20 B Building moved 1300mm away from existing walls
07.05.20 A Cavity barriers added to elevations



HALLIDAY FRASER MUNRO
CHARTERED ARCHITECTS & PLANNING CONSULTANTS

Project:
Broomhill Nursery
ELC Expansion Programme for ACC

Client:
Aberdeen City Council

Title:
Proposed Elevations

Document Reference
11462 - HFV - ZZ - DR - A - L(25) 001

Drawing Status:
Revision B
Billing
Scale: 1:50 @ A1
Date: Nov 2019

Do not scale this drawing.
Consent Survey material is reproduced with the permission of the controller of her Majesty's Stationary Office Crown Copyright reserved.

The copyright of this drawing subsists in Halliday Fraser Munro Ltd.
Registered Office:
8 Victoria Street,
Aberdeen, AB10 1XB
T: 01224 388 700
E: info@hfm.co.uk
W: hfm.co.uk

